

Submersible  
liquid level  
monitoring +/-  
0.05% Accuracy



Characteristic	Transmitter
Mounting	1inch BSP.
Medium	Adblue, Water, Kero, Diesel, Fertilizer, etc.
Accuracy	+/-0.5% (medium under measurement determins accuracy)
Diameter	27mm
Length	3M or 10M
Memory	The SG6 retains atleast five readings. The internet service retains all data
Logging Rate	Level data is transmitted to the internet services on a variable period once every 24 hours.
Sample Rate	Readings are checked every 3mins to detected changes. Alarms are trasnmitted instantly
Alarms	Fast drop and fill
Installation	GPS, Glonass and Galileo
Location	Internal Antenna Only
Antenna	Internal, external option for very low signal
Methods	GSM, GPRS, eMTC(LTE Cat-M1), NB IoT and Sigfox
Network Operator(s)	The smartgaurd supplied SIM and services allows all operators to be roamed at once ensuring maximum coverage- even worldwide.
Power	A replaceable spiral wound lithum battery. Up to 5 Years Life
Ambient Temperature	-20°C to +85°C
Size	65 x 80 x 80 mm
Ingress Protection	IP65
Colour	Black

Benefits



**Simple Assembly**  
Mounted quickly and fixed with simple screw holes. Suitable for all tank types.



**Save Costs**  
Investing in Smart Telemetry will allow you to better manage your Tanks consumption.



**High Accuracy**  
Regardless of the type of stored medium the sensor offers a 0.5% accuracy.



**Mobility**  
Full control with the Hastel SmartGuard Mobile App with Alexa compatibility




**Cloud-Based Technology**  
Access usage and level data anytime and anywhere



**Security**  
Automated theft Alerts as standard

Features



Threshold Alarms



Rapid Drop Detection and Theft Alarm



Fill Alerts



GPS Location and tracking



App and Google Play Compatible App



amazon alexa

Amazon Alexa Compatible